## MannTek



## Key benefits

- Easy to handle.
- Time saving.
- Economical.
- Safe.
- Environmentally friendly.
- Quality





## DGC

Loading and unloading of liquefied petroleum gas (LPG) and various other media.

- Dry gas couplings according to EN13760.
- Optimized for connection and disconnection at higher pressure (up to 25 bar).
- Sizes from 1" to 8".
- · Material: Stainless Steel.
- Seals: FKM/LT.
- Available with threaded and flanged connections, for both hose unit and tank unit.
- Working pressure: 25 bar.





## Technical data DGC













	1" (DN25)			2" (DN50)			3" (DN80)			4" (DN100)			6" (DN150)			8" (DN200)		
Socket	56 mm			70 mm			119 mm			164	164 mm			238 mm			272 mm	
Threaded connections	3/4", 1", 11/4" BSP, NPT, ACME			1½", 2" BSP, NPT, ACME			3" BSP, NPT, ACME			4" BSP, NPT, ACME			6" BSP, NPT, ACME		8" BSP, NPT, ACME			
Flanged connections	ANSI and	ANSI and EN. Others on request.																
Flow rate	Up to 250 L/min			Up to 900 L/min			Up to 2.800 L/min			Up to 7.000 L/min			Up to 14.000 L/min			Up to 23.000 L/min		
Materials	Stainless Steel	Thread	Flange	SS	Т	F	SS	Т	F		Т	F	SS	Т	F	SS	F	
		HU 2,1 kg TU 0.8 kg	HU - TU 1,8 kg		HU 3,7 kg TU 1,2 kg	HU 6,8 kg TU 4 kg		HU 9,5 kg TU 3 kg	HU 14,1 kg TU 7 kg		HU 16,1 kg TU 6 kg	HU 21,6 kg TU 15,2 kg		HU 45 kg TU 16,7 kg	HU 55,9 kg TU 23,8 kg		HU 95,4 kg TU 47,2 kg	
Seals	FKM/LT																	

